

Safety Data Sheet

POLYDUR ZINC

Safety Data Sheet dated 30/04/2024 version 5



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: POLYDUR ZINC

Trade code: L0040380

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Coatings and paints, thinners, paint removers

Stucco denso poliestere

Dispersione pigmentata fluida

Usi professionali

Uses advised against: N.A.

1.3. Details of the supplier of the safety data sheet

Company: Lechler SpA - Via Cecilio, 17 - 22100 Como - CO - Italy

Telefono: +39031586111

First Email: safety@lechler.eu

1.4. Emergency telephone number

CAV "Osp.Ped.Bambino Gesù" Dip.Emergenza di Roma ...0668593726
Azienda Ospedaliera Università di Foggia800183459 -
Ospedale Niguarda Ca' Granda di Milano0266101029 -
Azienda Ospedaliera "A. Cardarelli" di Napoli0817472870 -
CAV Policlinico "Umberto I" di Roma0649978000 -
CAV Policlinico "A. Gemelli" di Roma063054343 -
Azienda Osp."Careggi" U.O. Tossicologica di Firenze0557947819 -
CAV Centro Nazionale di Informaz.Tossicol. di Pavia038224444 -
Azienda Ospedaliera Papa Giovanni XXIII di Bergamo.....800883300 -
Azienda Ospedaliera Integrata di Verona..... ..800011858 -

SECTION 2: Hazards identification



2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

Flam. Liq. 3	Flammable liquid and vapour.
Skin Irrit. 2	Causes skin irritation.
Skin Sens. 1A	May cause an allergic skin reaction.
Eye Irrit. 2	Causes serious eye irritation.
Repr. 2	Suspected of damaging the unborn child.
STOT RE 1	Causes damage to organs through prolonged or repeated exposure.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Regulation (EC) No 1272/2008 (CLP):

Hazard pictograms and Signal Word



Danger

Hazard statements

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.

Precautionary statements

P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P405	Store locked up.
P501	Smaltire il prodotto/recipiente in un impianto autorizzato in conformità alla regolamentazione locale, regionale, nazionale e internazionale.

Special Provisions:

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Contains

stirene
anidride maleica

Special provisions according to Annex XVII of REACH and subsequent amendments:

None.

2.3. Other hazards

Risultati della valutazione PBT e vPvB

Secondo i criteri dell'ordinamento REACH nessuna sostanza come PBT, vPvB. Proprietà di interferenza con il sistema endocrino-Tossicità

La sostanza/miscela non contiene componenti considerati aventi proprietà di interferenza endocrina ai sensi dell'articolo 57(f) del REACH o del regolamento delegato (UE) 2017/2100 della Commissione o del regolamento (UE) 2018/605 della Commissione a livelli dello 0,1% o superiori.

Proprietà di interferenza con il sistema endocrino-Ecotossicità

La sostanza/miscela non contiene componenti considerati aventi proprietà di interferenza endocrina ai sensi dell'articolo 57(f) del REACH o del regolamento delegato (UE) 2017/2100 della Commissione o del regolamento (UE) 2018/605 della Commissione a livelli dello 0,1% o superiori.

Other Hazards: No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Mixture identification: POLYDUR ZINC

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Numb.	Classification	Registration Number
≥40 - ≤50 %	talco (Mg ₃ H ₂ (SiO ₃) ₄)	CAS:14807-96-6 EC:238-877-9	Substance with a Union workplace exposure limit.	
≥12.5 - ≤15 %	stirene	CAS:100-42-5 EC:202-851-5 Index:601-026-00-0	Flam. Liq. 3, H226; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; STOT RE 1, H372; Asp. Tox. 1, H304; Aquatic Chronic 3, H412; Repr. 2, H361	01-2119457861-32
≥10 - ≤12.5 %	diossido di titanio	CAS:13463-67-7 EC:236-675-5	Not classified as hazardous	01-2119489379-17

Index:022-006-00-2

≥7 - ≤10 %	bario solfato	CAS:7727-43-7 EC:231-784-4	Not classified as hazardous	01-2119491274-35
< 0.1 %	anidride maleica	CAS:108-31-6 EC:203-571-6 Index:607-096-00-9	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1A, H317 STOT RE 1, H372, EUH071	01-2119472428-31

Specific Concentration Limits:
C ≥ 0.001%: Skin Sens. 1A H317

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and label hazardous.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

Eye irritation

Eye damages

Skin Irritation

Erythema

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

CO2 or Dry chemical fire extinguisher.

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non emergency personnel:

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

For emergency responders:

Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

7.2. Conditions for safe storage, including any incompatibilities

Conservare ad una temperatura compresa tra 5° e 35°C. Tenere lontano da fiamme libere e sorgenti di calore. Evitare l'esposizione diretta al sole.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Community Occupational Exposure Limits (OEL)

	OEL Type	Country	Occupational Exposure Limit
talco (Mg ₃ H ₂ (SiO ₃) ₄) CAS: 14807-96-6	ACGIH		Long Term: 2 mg/m ³ Containing no asbestos fibers\$ E,R, A4 - Pulm fibrosis, pulm func
	EU		Long Term: 0.1 mg/m ³ 2004/37/CE
	SUVA	SWITZERLAN D	Long Term: 2 mg/m ³ Se il valore limite di esposizione professionale viene rispettato, le lesioni al feto sono improbabili.
	EU		Agenti cancerogeni o mutageni
	EU		Polvere respirabile
stirene CAS: 100-42-5	SUVA	SWITZERLAN D	Long Term: 85 mg/m ³ - 20 ppm ototossicità con amplificazione del rumore
	SUVA	SWITZERLAN D	Breve Termine 170 mg/m ³ - 40 ppm Se il valore limite di esposizione professionale viene rispettato, le lesioni al feto sono improbabili.
	ACGIH		Long Term: 10 ppm; Breve Termine 20 ppm OTO, A3, BEI - CNS and hearing impair, URT irr, peripheral neuropathy, visual disorders
diossido di titanio CAS: 13463-67-7	SUVA	SWITZERLAN D	Long Term: 3 mg/m ³ Polveri inerti, valore limite di esposizione professionale generale; Si qualificano come inerti le polveri che, allo stato attuale d
	ACGIH		Long Term: 0.2 mg/m ³ Nanoscale particles; R ; A3 - LRT irr, pneumoconiosis

	ACGIH		Long Term: 2.5 mg/m ³ Finescale particles; R ; A3 - LRT irr, pneumoconiosis
bario solfato CAS: 7727-43-7	ACGIH		Long Term: 5 mg/m ³ I, E - Pneumoconiosis
anidride maleica CAS: 108-31-6	SUVA	SWITZERLAN D	Breve Termine 0.4 mg/m ³ - 0.1 ppm Occupational Safety and Health Administration
	SUVA	SWITZERLAN D	Long Term: 0.4 mg/m ³ - 0.1 ppm La sostanza può essere presente contemporaneamente come vapore e aerosol
	ACGIH		Long Term: 0.01 mg/m ³ IFV, DSEN, RSEN, A4 - Resp sens

Biological limit values

stirene
CAS: 100-42-5

Biological Indicator: mandelic acid; Sampling Period: Fine turno
Value: 800 mg/g Creatinine; Medium: Urine
Remark: Argentina. Biological Exposure Indices

Biological Indicator: mandelic acid; Sampling Period: Before next shift
Value: 300 mg/g Creatinine; Medium: Urine
Remark: Argentina. Biological Exposure Indices

Biological Indicator: phenyl glycolic acid; Sampling Period: Fine turno
Value: 240 mg/g Creatinine; Medium: Urine
Remark: Argentina. Biological Exposure Indices

Biological Indicator: phenyl glycolic acid; Sampling Period: Before next shift
Value: 100 mg/g Creatinine; Medium: Urine
Remark: Argentina. Biological Exposure Indices

Biological Indicator: styrene; Sampling Period: Fine turno
Value: 0.55 mg/L; Medium: Blood
Remark: Argentina. Biological Exposure Indices

Biological Indicator: styrene; Sampling Period: Before next shift
Value: 0.02 mg/L; Medium: Blood
Remark: Argentina. Biological Exposure Indices

Biological Indicator: mandelic acid; Sampling Period: End of last day of the working day (recommended to avoid the first day of the week)
Value: 8 g/g creatinine; Medium: Urine
Remark: Brazil. NR7. Parameters for Biological Control of Occupational Exposure to Some Chemical Agents

Biological Indicator: phenyl glyoxylic acid; Sampling Period: End of last day of the working day (recommended to avoid the first day of the week)
Value: 240 mg/g Creatinine; Medium: Urine
Remark: Brazil. NR7. Parameters for Biological Control of Occupational Exposure to Some Chemical Agents

Biological Indicator: total mandelic acid plus phenylglyoxylic acid; Sampling Period: In case of long-term exposure: after more than one shift
Value: 600 mg/g Creatinine; Medium: Urine
Remark: Bulgaria. Biological limit values

Biological Indicator: mandelic acid; Sampling Period: Fine turno
Value: 800 mg/g Creatinine; Medium: Urine
Remark: Chile. Biological Limit Values

Biological Indicator: phenyl glyoxylic acid; Sampling Period: Fine turno
Value: 240 mg/g Creatinine; Medium: Urine
Remark: Chile. Biological Limit Values

Biological Indicator: Mandelic acid and phenylglyoxylic; Sampling Period: Fine turno
Value: 295 Millimoles per mole Creatinine; Medium: Urine
Remark: China. Biological Occupational Exposure Limits for 15 chemicals.

Biological Indicator: Mandelic acid and phenylglyoxylic; Sampling Period: Fine turno
Value: 400 mg/g Creatinine; Medium: Urine
Remark: China. Biological Occupational Exposure Limits for 15 chemicals.

Biological Indicator: Mandelic acid and phenylglyoxylic; Sampling Period: Before next shift
Value: 120 Millimoles per mole Creatinine; Medium: Urine
Remark: China. Biological Occupational Exposure Limits for 15 chemicals.

Biological Indicator: Mandelic acid and phenylglyoxylic; Sampling Period: Before next shift
Value: 160 mg/g Creatinine; Medium: Urine
Remark: China. Biological Occupational Exposure Limits for 15 chemicals.

Biological Indicator: Mandelic acid and phenylglyoxylic; Sampling Period: Fine turno
Value: 400 mg/g Creatinine; Medium: Urine
Remark: Maximum allowable occupational exposure limits in the workplace - Table 3. Adopted Biological Exposu

Biological Indicator: Styrene; Sampling Period: Fine turno
Value: 40 µg/L; Medium: Urine
Remark: Maximum allowable occupational exposure limits in the workplace - Table 3. Adopted Biological Exposu

Biological Indicator: styrene; Sampling Period: 16 Hours after the end of work
Value: 19 micromol per litre; Medium: Blood
Remark: Croatia. Biological Exposure Limits

Biological Indicator: styrene; Sampling Period: 16 Hours after the end of work
Value: 20 µg/L; Medium: Blood
Remark: Croatia. Biological Exposure Limits

Biological Indicator: mandelic acid; Sampling Period: Fine turno
Value: 1 g/g creatinine; Medium: Urine
Remark: Croatia. Biological Exposure Limits

Biological Indicator: mandelic acid; Sampling Period: Fine turno
Value: 74 mol/mol creatinine; Medium: Urine
Remark: Croatia. Biological Exposure Limits

Biological Indicator: phenyl glyoxylic acid; Sampling Period: Fine turno
Value: 240 mg/g Creatinine; Medium: Urine
Remark: Croatia. Biological Exposure Limits

Biological Indicator: phenyl glyoxylic acid; Sampling Period: Fine turno
Value: 18 mol/mol creatinine; Medium: Urine
Remark: Croatia. Biological Exposure Limits

Biological Indicator: mandelic acid + phenyl glyoxylic acid; Sampling Period: during long-term exposure in the middle of the work week
Value: 600 mg/g Creatinine; Medium: Urine
Remark: Croatia. Biological Exposure Limits

Biological Indicator: mandelic acid; Sampling Period: Fine turno
Value: 400 mg/g Creatinine; Medium: Urine
Remark: Czech Republic. Biological Exposure Indices

Biological Indicator: mandelic acid; Sampling Period: Fine turno
Value: 300 micromoles per millimole creatinine; Medium: Urine
Remark: Czech Republic. Biological Exposure Indices

Biological Indicator: mandelic + phenylglyoxilic acid; Sampling Period: Fine turno
Value: 600 mg/g Creatinine; Medium: Urine
Remark: Czech Republic. Biological Exposure Indices

Biological Indicator: MAPGA; Sampling Period: Morning after working day
Value: 1.2 mg/L; Medium: Urine
Remark: Finland. Biological limit values

Biological Indicator: mandelic acid + phenylglyoxylic acid; Sampling Period: Immediately after exposure or after working hours
Value: 600 mg/g Creatinine; Medium: Urine
Remark: TRGS 903 - Biological limit values

Biological Indicator: mandelic acid; Sampling Period: FSL
Value: 1000 mg/g Creatinine; Medium: Urine
Remark: Hungary. Permissible limit values of biological exposure (effect) indices

Biological Indicator: mandelic acid; Sampling Period: After shift
Value: 740 micromoles per millimole creatinine; Medium: Urine
Remark: Hungary. Permissible limit values of biological exposure (effect) indices

Biological Indicator: Mandelic acid and phenylglyoxylic; Sampling Period: FSL
Value: 400 mg/g Creatinine; Medium: Urine
Remark: Israel. Safety at Work Regulations - Annex III Biological Exposure Indices

Biological Indicator: Mandelic acid + Phenylglyoxylic acid; Sampling Period: Fine turno; Fine settimana lavorativa
Value: 430 mg/L; Medium: Urine
Remark: Occupational exposure limits based on biological monitoring (JSOH).

Biological Indicator: Styrene; Sampling Period: Fine turno; Fine settimana lavorativa
Value: 0.2 mg/L; Medium: Blood
Remark: Occupational exposure limits based on biological monitoring (JSOH).

Biological Indicator: Mandelic acid; Sampling Period: Fine turno
Value: 800 mg/g Creatinine; Medium: Urine
Remark: Kenya. Occupational Safety and Health Act (CAP.514), Schedule I, Table 3 Biological Exposure Limits

Biological Indicator: Mandelic acid; Sampling Period: Before next shift
Value: 300 mg/g Creatinine; Medium: Urine
Remark: Kenya. Occupational Safety and Health Act (CAP.514), Schedule I, Table 3 Biological Exposure Limits

Biological Indicator: Phenylglyoxylic acid; Sampling Period: Fine turno
Value: 240 mg/g Creatinine; Medium: Urine
Remark: Kenya. Occupational Safety and Health Act (CAP.514), Schedule I, Table 3 Biological Exposure Limits

Biological Indicator: Phenylglyoxylic acid; Sampling Period: Before next shift
Value: 100 mg/g Creatinine; Medium: Urine
Remark: Kenya. Occupational Safety and Health Act (CAP.514), Schedule I, Table 3 Biological Exposure Limits

Biological Indicator: Styrene; Sampling Period: Fine turno
Value: 0.55 mg/L; Medium: venous blood
Remark: Kenya. Occupational Safety and Health Act (CAP.514), Schedule I, Table 3 Biological Exposure Limits

Biological Indicator: Styrene; Sampling Period: Before next shift
Value: 0.02 mg/L; Medium: venous blood
Remark: Kenya. Occupational Safety and Health Act (CAP.514), Schedule I, Table 3 Biological Exposure Limits

Biological Indicator: mandelic acid; Sampling Period: Fine turno
Value: 8 g/g creatinine; Medium: Urine
Remark: Latvia. Biological Exposure Indices

Biological Indicator: styrene; Sampling Period: Fine turno
Value: 0.55 mg/L; Medium: Blood
Remark: Latvia. Biological Exposure Indices

Biological Indicator: Mandelic acid and phenylglyoxylic; Sampling Period: Fine turno
Value: 400 mg/g Creatinine; Medium: Urine
Remark: Official Mexican Norm NOM-047-SSA1-2011, Environmental Health - Biological exposure indices for work

Biological Indicator: Styrene; Sampling Period: Fine turno
Value: 0.2 mg/L; Medium: venous blood
Remark: Official Mexican Norm NOM-047-SSA1-2011, Environmental Health - Biological exposure indices for work

Biological Indicator: Mandelic acid; Sampling Period: Fine turno
Value: 1 Millimoles per liter; Medium: Urine
Remark: New Zealand. Biological Exposure Indices

Biological Indicator: Sum of mandelic acid and phenyl glyoxylic acid; Sampling Period: Fine turno
Value: 400 mg/g Creatinine; Medium: Urine
Remark: Portuguese Norm 1796 - Biological Exposure Indices

Biological Indicator: Styrene; Sampling Period: Fine turno
Value: 0.2 mg/L; Medium: venous blood
Remark: Portuguese Norm 1796 - Biological Exposure Indices

Biological Indicator: mandelic acid; Sampling Period: Fine turno
Value: 800 mg/g Creatinine; Medium: Urine
Remark: Romania. Biological limit values

Biological Indicator: mandelic acid; Sampling Period: Beginning of next shift
Value: 300 mg/g Creatinine; Medium: Urine
Remark: Romania. Biological limit values

Biological Indicator: phenylglyoxalic acid; Sampling Period: Fine turno
Value: 100 mg/g Creatinine; Medium: Urine
Remark: Romania. Biological limit values

Biological Indicator: styrene; Sampling Period: Fine turno
Value: 0.55 mg/L; Medium: Blood
Remark: Romania. Biological limit values

Biological Indicator: styrene; Sampling Period: Beginning of next shift
Value: 0.02 mg/L; Medium: Blood
Remark: Romania. Biological limit values

Biological Indicator: Mandelic acid and phenylglyoxylic; Sampling Period: Fine turno
Value: 901 mg/L; Medium: Urine
Remark: Slovakia. Biological Limit Values

Biological Indicator: Mandelic acid and phenylglyoxylic; Sampling Period: In case of long-term exposure:
after more than one shift
Value: 5960 micromol per litre; Medium: Urine
Remark: Slovakia. Biological Limit Values

Biological Indicator: Mandelic acid and phenylglyoxylic; Sampling Period: Fine turno
Value: 600 mg/g Creatinine; Medium: Urine
Remark: Slovakia. Biological Limit Values

Biological Indicator: Mandelic acid and phenylglyoxylic; Sampling Period: In case of long-term exposure:
after more than one shift
Value: 449 micromoles per millimole creatinine; Medium: Urine
Remark: Slovakia. Biological Limit Values

Biological Indicator: Mandelic acid and phenylglyoxylic; Sampling Period: Fine turno
Value: 600 mg/g Creatinine; Medium: Urine
Remark: Slovenia. BAT-values

Biological Indicator: Mandelic acid; Sampling Period: Fine turno
Value: 800 mg/g Creatinine; Medium: Urine
Remark: South Africa. Hazardous Chemical Substances Regulations, Biological Exposure Indices.

Biological Indicator: Mandelic acid; Sampling Period: Before next shift
Value: 300 mg/g Creatinine; Medium: Urine
Remark: South Africa. Hazardous Chemical Substances Regulations, Biological Exposure Indices.

Biological Indicator: Phenolglyoxylic acid; Sampling Period: Fine turno
Value: 240 mg/g Creatinine; Medium: Urine
Remark: South Africa. Hazardous Chemical Substances Regulations, Biological Exposure Indices.

Biological Indicator: Phenolglyoxylic acid; Sampling Period: Before next shift
Value: 100 mg/g Creatinine; Medium: Urine
Remark: South Africa. Hazardous Chemical Substances Regulations, Biological Exposure Indices.

Biological Indicator: Styrene; Sampling Period: Fine turno
Value: 0.55 mg/L; Medium: venous blood
Remark: South Africa. Hazardous Chemical Substances Regulations, Biological Exposure Indices.

Biological Indicator: Styrene; Sampling Period: Before next shift
Value: 0.02 mg/L; Medium: venous blood
Remark: South Africa. Hazardous Chemical Substances Regulations, Biological Exposure Indices.

Biological Indicator: Mandelic acid and phenylglyoxylic; Sampling Period: End of workday
Value: 400 mg/g Creatinine; Medium: Urine
Remark: Occupational Exposure Limits for Chemical Agents in Spain - Biological Exposure Values

Biological Indicator: styrene; Sampling Period: End of workday
Value: 0.2 mg/L; Medium: venous blood
Remark: Occupational Exposure Limits for Chemical Agents in Spain - Biological Exposure Values

Biological Indicator: Mandelic acid and phenylglyoxylic; Sampling Period: Immediately after exposure or
after working hours
Value: 600 mg/g Creatinine; Medium: Urine
Remark: Svizzera. Lista di valori BAT

Biological Indicator: Mandelic acid and phenylglyoxylic; Sampling Period: End of workday
Value: 400 mg/g Creatinine; Medium: Urine
Remark: Uruguay. Health surveillance of workers - Biological Exposure Indices (BEI).

Biological Indicator: styrene; Sampling Period: End of workday
Value: 0.2 mg/L; Medium: Blood
Remark: Uruguay. Health surveillance of workers - Biological Exposure Indices (BEI).

Biological Indicator: Mandelic acid and phenylglyoxylic; Sampling Period: Fine turno
Value: 400 mg/g Creatinine; Medium: Urine
Remark: ACGIH - Indicatori di Esposizione Biologica (BEI)

Biological Indicator: Styrene; Sampling Period: Fine turno
Value: 40 µg/L; Medium: Urine
Remark: ACGIH - Indicatori di Esposizione Biologica (BEI)

Biological Indicator: Mandelic acid; Sampling Period: End of workday
Value: 400 mg/g Creatinine; Medium: Urine
Remark: VE. Biological Exposure Limits

Biological Indicator: Styrene; Sampling Period: End of workday

Value: 0.2 mg/L; Medium: Blood
Remark: VE.Biological Exposure Limits

Sampling Period: during long-term exposure: at the end of the work shift after several consecutive workdays

Sampling Period: Fine turno

Sampling Period: In case of long-term exposure: after more than one shift

Sampling Period: Fine turno

Sampling Period: In case of long-term exposure: after more than one shift

Sampling Period: After shift

Sampling Period: In case of long-term exposure: after more than one shift

Sampling Period: Fine turno

Predicted No Effect Concentration (PNEC) values

stirene
CAS: 100-42-5

Exposure Route: Fresh Water; PNEC Limit: 0.028 mg/l

Exposure Route: Marine water; PNEC Limit: 0.014 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 0.614 mg/kg

Exposure Route: Marine water sediments; PNEC Limit: 0.307 mg/kg

Exposure Route: Soil; PNEC Limit: 0.2 mg/kg

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 5 mg/l

diossido di titanio
CAS: 13463-67-7

Exposure Route: Fresh Water; PNEC Limit: 1 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 1000 mg/kg

Exposure Route: Marine water; PNEC Limit: 0.127 mg/l

Exposure Route: Marine water sediments; PNEC Limit: 100 mg/kg

Exposure Route: Soil; PNEC Limit: 100 mg/kg

bario solfato
CAS: 7727-43-7

Exposure Route: Fresh Water; PNEC Limit: 0.115 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 600.4 mg/kg

Exposure Route: Soil; PNEC Limit: 207.7 mg/kg

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 62.6 mg/l

Derived No Effect Level (DNEL) values

stirene
CAS: 100-42-5

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Professional: 406 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Professional: 85 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects
Worker Professional: 289 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Short Term (acute)
Worker Professional: 306 mg/m³

Exposure Route: Oral; Exposure Frequency: Long Term, systemic effects
Consumer: 2.1 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Consumer: 343 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Consumer: 10 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects
Consumer: 174.25 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Short Term (acute)
Consumer: 182.75 mg/m³

diossido di titanio
CAS: 13463-67-7

Exposure Route: Human Inhalation; Exposure Frequency: Local Effects
Worker Professional: 10 mg/m³

Exposure Route: Human Oral; Exposure Frequency: Specific Effects
Consumer: 700 ppm

bario solfato
CAS: 7727-43-7

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Professional: 10 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Professional: 10 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Consumer: 10 mg/m³

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
Consumer: 13000 mg/kg

8.2. Exposure controls

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use adequate protective respiratory equipment.

Thermal Hazards:

N.A.

Environmental exposure controls:

N.A.

Hygienic and Technical measures

N.A.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid

Colour: beige

Odour: N.A.

pH: Not Relevant

Kinematic viscosity: > 20,5 mm²/sec (40 °C)

Melting point/freezing point: N.A.

Boiling point or initial boiling point and boiling range: N.A.

Flash point: 23°C / 60°C

Lower and upper explosion limit: N.A.

Relative vapour density: N.A.

Vapour pressure: N.A.

Density and/or relative density: 1.80 g/cm³

Solubility in water: N.A.

Solubility in oil: N.A.

Partition coefficient n-octanol/water (log value): N.A.

Auto-ignition temperature: N.A.

Decomposition temperature: N.A.

Flammability: The product is classified Flam. Liq. 3 H226

Kinematic viscosity m²/s (40°C) > 20,5 mm²/sec (40 °C)

Viscosity: = 65.00 s - Method: ISO/DIN 2431 84 - Sezione: 6.00 mm

Particle characteristics:

Particle size: N.A.

9.2. Other information

Evaporation rate: N.A.

Miscibility: N.A.

Conductivity: N.A.

No other relevant information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Data not available.

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological Information of the Preparation

a) acute toxicity	Not classified
	Based on available data, the classification criteria are not met
b) skin corrosion/irritation	The product is classified: Skin Irrit. 2(H315)
c) serious eye damage/irritation	The product is classified: Eye Irrit. 2(H319)
d) respiratory or skin sensitisation	The product is classified: Skin Sens. 1A(H317)
e) germ cell mutagenicity	Not classified
	Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified
	Based on available data, the classification criteria are not met
g) reproductive toxicity	The product is classified: Repr. 2(H361)
h) STOT-single exposure	Not classified
	Based on available data, the classification criteria are not met
i) STOT-repeated exposure	The product is classified: STOT RE 1(H372)
j) aspiration hazard	Not classified
	Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

talco (Mg ₃ H ₂ (SiO ₃) ₄)	a) acute toxicity	LD50 Oral > 5000 mg/kg bw	
stirene	a) acute toxicity	LD50 Oral Ratto = 5000 mg/kg LC50 Inhalation Ratto = 11.8 mg/l 4h LD50 Skin Ratto > 2000 mg/kg	OECD Test Guideline 402
diossido di titanio	a) acute toxicity	LD50 Oral Ratto > 5000 mg/kg LD50 Skin Coniglio > 5000 mg/kg	

11.2. Information on other hazards

Endocrine disrupting properties:

La sostanza/miscela non contiene componenti considerati aventi proprietà di interferenza endocrina ai sensi dell'articolo 57(f) del REACH o del regolamento delegato (UE) 2017/2100 della Commissione o del regolamento (UE) 2018/605 della Commissione a livelli dello 0,1% o superiori.

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

Not classified for environmental hazards.

No data available for the product

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
stirene	CAS: 100-42-5 - EINECS: 202- 851-5 - INDEX: 601-026-00-0	a) Tossicità acquatica acuta : LC50 Fish Pimephales promelas (fathead minnow) = 4.02 mg/L 96 H

a) Tossicità acquatica acuta : EC50 Invertebrates Daphnia magna (Water flea) = 4.7 mg/L 48 H

e) Tossicità per le piante : EC10 Algae Pseudokirchneriella subcapitata (microalgae) = 0.28 mg/L 96 H

b) Tossicità acquatica cronica : NOEC Invertebrates Daphnia magna (Water flea) = 1.01 mg/L 21 D

e) Tossicità per le piante : EC50 Algae Pseudokirchneriella subcapitata (microalgae) = 4.9 mg/L 72 H

diossido di titanio

CAS: 13463-67-7 - EINECS: 236-675-5 - INDEX: 022-006-00-2

a) Tossicità acquatica acuta : LC50 Fish > 100 mg/L 96h

a) Tossicità acquatica acuta : EC50 Daphnia > 100 mg/L 48h

12.2. Persistence and degradability

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

No PBT or vPvB substances present in concentration \geq 0.1%

12.6. Endocrine disrupting properties

La sostanza/miscela non contiene componenti considerati aventi proprietà di interferenza endocrina ai sensi dell'articolo 57(f) del REACH o del regolamento delegato (UE) 2017/2100 della Commissione o del regolamento (UE) 2018/605 della Commissione a livelli dello 0,1% o superiori.

12.7. Other adverse effects

N.A.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

SECTION 14: Transport information

14.1. UN number or ID number

3269

14.2. UN proper shipping name

ADR-Shipping Name: POLYESTER RESIN KIT

IATA-Technical name: POLYESTER RESIN KIT liquid base material

IMDG-Technical name: POLYESTER RESIN KIT, liquid base material

14.3. Transport hazard class(es)

ADR-Class: 3

IATA-Class: 3

IMDG-Class: 3

14.4. Packing group

ADR-Packing Group: III

IATA-Packing group: III

IMDG-Packing group: III

14.5. Environmental hazards

Marine pollutant: No

Environmental Pollutant: No

IMDG-EMS: F-E, S-D

14.6. Special precautions for user

Road and Rail (ADR-RID):

ADR-Label: 3

ADR - Hazard identification number: -

ADR-Special Provisions: 236 340

ADR-Transport category (Tunnel restriction code): 3 (E)

Air (IATA):

IATA-Passenger Aircraft: 370

IATA-Cargo Aircraft: 370

IATA-Label: 3

IATA-Subsidiary hazards: -

IATA-Erg: 3L

IATA-Special Provisions: A66 A163

Sea (IMDG):

IMDG-Stowage Code: Category A

IMDG-Stowage Note: -

IMDG-Subsidiary hazards: -

IMDG-Special Provisions: 236 340

14.7. Maritime transport in bulk according to IMO instruments

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Regulation (EU) n. 2021/643 (ATP 16 CLP)

Regolamento (UE) n. 2021/849 (ATP 17 CLP)

Regolamento (UE) n. 2022/692 (ATP 18 CLP)

Regulation (EU) n. 2020/878

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: 3, 40

Restrictions related to the substances contained: 75

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1	Lower-tier threshold (tonnes)	Upper-tier threshold (tonnes)
--	-------------------------------	-------------------------------

Product belongs to category: P5c	5000	50000
----------------------------------	------	-------

Regulation (EU) No 649/2012 (PIC regulation)

No substances listed

German Water Hazard Class.

2: significativamente inquinante per le acque

Lagerklasse according to TRGS 510:

LGK 3

SVHC Substances:

NOSVHCCOMPS

Dir. 2010/75/CE (Direttiva COV)

Volatile Organic compounds - VOCs = 13.85 %

Volatile Organic compounds - VOCs = 249.30 g/L

Estimated Total Content of Water 0.00 %

Estimated Total Solid Content 86.15 %

Classificazione in accordo con VbF

Classificazione in accordo con VbF Esente

Mal-Code (Denmark)

Mal-Code (Denmark)	Mal Factor	Unit of Measure	Revision Status / Number	Regulatory Base
4 - 6	2.950	m3 air/10 g	1993	Administrative determined MAL-Factors

Biocidi

REGOLAMENTO (CE) N. 528/2012

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Code	Description
EUH071	Corrosive to the respiratory tract.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H361	Suspected of damaging fertility or the unborn child.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H372	Causes damage to organs (hearing organs) through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
2.6/3	Flam. Liq. 3	Flammable liquid, Category 3
3.1/4/Inhal	Acute Tox. 4	Acute toxicity (inhalation), Category 4
3.1/4/Oral	Acute Tox. 4	Acute toxicity (oral), Category 4
3.10/1	Asp. Tox. 1	Aspiration hazard, Category 1
3.2/1B	Skin Corr. 1B	Skin corrosion, Category 1B
3.2/2	Skin Irrit. 2	Skin irritation, Category 2
3.3/1	Eye Dam. 1	Serious eye damage, Category 1
3.3/2	Eye Irrit. 2	Eye irritation, Category 2
3.4.1/1	Resp. Sens. 1	Respiratory Sensitisation, Category 1
3.4.2/1A	Skin Sens. 1A	Skin Sensitisation, Category 1A
3.7/2	Repr. 2	Reproductive toxicity, Category 2
3.8/3	STOT SE 3	Specific target organ toxicity — single exposure, Category 3
3.9/1	STOT RE 1	Specific target organ toxicity — repeated exposure, Category 1
4.1/C3	Aquatic Chronic 3	Chronic (long term) aquatic hazard, category 3

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008**[CLP]:****Classification according to Regulation Classification procedure**

(EC) Nr. 1272/2008

Flam. Liq. 3, H226	On basis of test data
Skin Irrit. 2, H315	Calculation method
Skin Sens. 1A, H317	Calculation method
Eye Irrit. 2, H319	Calculation method
Repr. 2, H361d	Calculation method
STOT RE 1, H372	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor

BEI: Biological Exposure Index

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand

COV: Volatile Organic Compound

CSA: Chemical Safety Assessment

CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive

DSD: Dangerous Substances Directive

EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.

ES: Exposure Scenario

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

IC50: half maximal inhibitory concentration

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

IMDG: International Maritime Code for Dangerous Goods.

INCI: International Nomenclature of Cosmetic Ingredients.

IRCCS: Scientific Institute for Research, Hospitalization and Health Care

KAFH: KAFH

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LDLo: Leathal Dose Low

N.A.: Not Applicable

N/A: Not Applicable

N/D: Not defined/ Not available

NA: Not available

NIOSH: National Institute for Occupational Safety and Health
NOAEL: No Observed Adverse Effect Level
OSHA: Occupational Safety and Health Administration
PBT: Persistent, Bioaccumulative and Toxic
PGK: Packaging Instruction
PNEC: Predicted No Effect Concentration.
PSG: Passengers
RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
TLV: Threshold Limiting Value.
TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
vPvB: Very Persistent, Very Bioaccumulative.
WGK: German Water Hazard Class.

Paragraphs modified from the previous revision:

- SECTION 2: Hazards identification
- SECTION 3: Composition/information on ingredients
- SECTION 7: Handling and storage
- SECTION 8: Exposure controls/personal protection
- SECTION 9: Physical and chemical properties
- SECTION 11: Toxicological information
- SECTION 12: Ecological information
- SECTION 14: Transport information
- SECTION 15: Regulatory information
- SECTION 16: Other information